



### KEY FACTS

- Available in different sizes suitable for the carrier vehicle.
- Plug-and-crack connection.
- Optimal cost/benefit ratio.
- Premium pin bearing.
- Robust and proven technology – Low-wear and low-service.
- KTL-primed (cathodic dip-coating) and powder coating. Made of high-strength Hardox® steel.



Thanks to the possible attachment to excavators, the log can be split and loaded in one single operation.





Various mounting options.



Low effort for splitting.

TECHNICAL DATA



Technical data and illustrations are not binding. Subject to changes for reasons of further development.

APPLICATION AREAS

- Splitting thick wood trunks.
- Pre-splitting wood allows a natural drying process and therefore increases biomass quality and energy yield.
- Can be used in all harvesting and processing methods of strong wood.
- Pre-splitting wood for further processing of split logs or chipped wood material.
- Easy supply of the pre-split material to chippers.
- Wood splitter can be used as a gripper.



The trunk can be split and loaded in one work step.



Splitting thick wood trunks.

PATENTED

WOODCRACKER® L	L 540	L 700	L 920	L 1200
Tongs opening (in)	21	28	35	47
Splitting force (depending on operating pressure) (tons)	up to 14	up to 22	upt to 22	up to 33
Deadweight (lbs)	430	630	820	2,400
Recommended pump flow capacity <sup>1)</sup> (gpm)	approx. 7 - 16	approx. 7 - 16	approx. 7 - 16	approx. 21 - 40
Recommended operating pressure <sup>1)</sup> (psi)	2,600 - 3,500	2,600 - 3,500	2,600 - 3,500	3,200 - 3,900
Optional: Standing fixture	•	•	•	•
Optional: Excavator attachment	•	•	•	-
Optional: Farm loader attachment	•	•	-	-

<sup>1)</sup> Depending on operating mode or equipment. <sup>2)</sup> Depending on specifications of the operation vehicle. • available - not available