

WOODCRACKER® CS flexHead



VIDEO

TURN YOUR TRUCK INTO A FELLING MACHINE!

TECHNICAL DATA



WOODCRACKER® CS flexHead®	CS590 flexHead ²
Cutting diameter (in)	23.6
Gripper opening (in)	50
Deadweight (fully equipped) ¹⁾ (lbs)	1.565
Recommended pump flow capacity ¹⁾ (gpm.)	13 - 24
Recommended operating pressure (psi)	3,300 - 4,350
Angle of motion vertically (degree)	160
Saw unit	rigid
Chain lubrication of saw	oil
Tiltator	endlessly rotatable
Automatic chain tensioner	available
Quick chain change system	available

FAST ON SITE. PRECISE IN TREE FELLING.

VARIOUS MOUNTING OPTIONS

STRONG TILTATOR


machine is endlessly rotatable

PLUG & PLAY

quick and easy installation

AUTOMATIC CHAIN TENSIONER

POWERFUL GRAPPLE



flexHead²

Rotation and vertical axis.



CHECK OUT YOUR BENEFITS!

- Reach every angle you need. Perfect for horizontal limbs.
- Ideal for removing sections from tree crowns.
- Innovative hydraulics allow sections to be removed in a standing position.
- Safe working method for operators.
- Quick set-up at the respective construction site. Fast on the road.
- Various attachment options.
- Robust and proven technology – Low-wear and low-service.
- Made of high-strength Hardox® steel.



Woodcracker® CS590 flexHead² for tree care.